

CERTIFICATE OF COMPLIANCE

Certificate Number E194432
Report Reference E194432-20000714
Issue Date 2020-JUNE-30

Issued to: BUD INDUSTRIES
4605 E 355TH ST
WILLOUGHBY OH 44094-4629

This certificate confirms that representative samples of INDUSTRIAL CONTROL PANELS
See Addendum.

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 508A, Industrial Control Panels.
CSA C22.2 No. 14-18, Industrial Control Equipment.

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E194432
Report Reference E194432-20000714
Issue Date 2020-JUNE-30

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Industrial Control Panel Enclosures

Aluminum, Type 4X, 12 and 13, Type AN followed by 1300 through 1323, may be followed by –G or followed by –B. Type AN followed by 2800 through 2823, and 2850 through 2873, may be followed by –B or –G.

Aluminum, Type 4, 4X, 6, 6P, Type AN followed by 1300 through 1323, may be followed by –A or –AG or –G or –AB or by -B. Type AN followed by 2800 through 2823, and 2850 through 2873, may be followed by –A or –AG or –G or –AB or by -B. (when using Inoac E4382 EPDM gasket)


Aluminum, Type 4, 4X, 6, 6P, 12, and/or 13, Type AN followed by 1300 through 1323, may be followed by –A or –AG or –G or –AB or -B. Type AN followed by 2800 through 2823, and 2850 through 2873, may be followed by –A or –AB or -B or –AG or -G. (when using Shin Etsu KE-9X1 Silicone gasket)

Polycarbonate, Type 4X, 6, 6P, 12 or 13, Type PN followed by 1320 through 1345, may be followed by –C, -AC, may be followed by MB, -AMB.

ABS, Type 4X Indoor, Type PN followed by 1320 through 1345, followed by –DG, may be followed by MB.

Polycarbonate, Type 4X, 6, 6P, 12 or 13, Type PNR followed by 2600 through 2608, may be followed by –C.

ABS, Type 4X Indoor, Type PNR followed by 2600 through 2608, followed by DG.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

