








## NOTES:

1. MATERIAL AND FLAMMABILITY RATING.  
BODY -PC LIGHT GRAY POLYCARBONATE - UL94-5VA  
COVER - PC LIGHT GRAY POLYCARBONATE - UL94-5VA  
CLEAR COVER (C) - PC CLEAR POLYCARBONATE - UL94-V0 AND TESED  
TO PASS 5VA PER UL746C
2. FOLLOW ENCLOSED INSTRUCTION FOR UL COMPLIANCE.: BOXES UL LISTED NEMA TYPE 1, 2, 3, 3R, 4, 4X, 5, 6, 6P 12, 13. DESIGNED MEETS IP65, IP66, IP67, IP68 REQUIREMENTS. UV RESISTANT FOR OUT DOOR USE.
3. OPERATING TEMPERATURE IS -35 TO 110C.
4. PRE INSTALLED SILICONE GASKET IN COVER
5. BOX COMES WITH
  - 4 UNINSTALLED MOUNTING BRACKETS
  - HARDWARE : 8 SCREWS & 4 PLUGS
6. OPTIONAL ACCESSORIES:
  - HINGE AND PANEL SUPPENSION KIT (DPX-444KIT)
  - 6" FLANGE KIT (2 FLANGES + 4 SCREWS) (DPX-624KIT)
  - BASE INTERNAL MOUNTING PANEL (DPX-287081)
  - HINGED INTERNAL MOUNTING PANEL (DPX-287082)
  - COVER MOUNTING PANEL (DPX-287083)
  - FLOATING INTERNAL MOUNTING PANEL (DPX-287084)
7. DIMENSIONS ARE INCH



## DRAWING FOR REFERENCE

WE RESERVE THE RIGHT TO MAKE CHANGES TO OUR STANDARD PRODUCTS. PLEASE CONSULT WITH BUD INDUSTRIES PRIOR TO USING THIS DRAWING FOR DESIGN PURPOSE.